DK POWER BY MARLON. V2 SERIES

6-INCH 19.5HP 500CC

KINETIC DRUM CHIPPER SHREDDER WITH ELECTRIC START

SKU # OPC566E-V2 | UPC # 990492500044

ELECTRIC START



DESCRIPTION

The OPC566E-V2 Kinetic Chipper is powered by a 19.5 HP 500 cc OHV engine, and deteriorates any tree up to 6.25 inches in diameter. Its bearing-mounted chipping drum system, oversized discharge height, and heavy-duty tow-behind frame make this machine an easy choice for large land clearing projects. The OPC566E-V2 is also OSHA-compliant with an extended infeed chute equipped with a safety stop bar, ignition lockout keys, and safety lockout contactors on both infeed and discharge chutes.

SPECIFICATION

ENGINE	19.5HP 500cc OHV with electric start
TORQUE	22.8 ft.-lbs. (31Nm) net torque
WHEELS	D.O.T. approved 19 x 7.00-8 (rear), 13 x 5.00-6 (front)
AXLE LENGTH	43.1" (109.5 cm) including wheels
CHIPPING CAPACITY	Ø6.25" (Ø15.9 cm)
CUTTERS	2 x 12" (30.5 cm) reversible steel chipper blades
DRUM ACCESS	Tool-free swing-open chutes with safety lockout contactors
CHIP RATIO	20:1
EXPULSION	61" (155 cm) height with 180° adjustable spout
COUPLER	2" (5.08 cm)
SOUND LEVEL	120 dB
DIMENSIONS	105.5" (L) x 40.6" (W) x 61" (H) 268 cm (L) x 103 cm (W) x 155 cm (H)
WEIGHT	555.6 lbs (252 kg)
SHIPPING DIMENSIONS	45.3" (L) x 30.7" (W) x 48.4" (H) 115 cm (L) x 78 cm (W) x 123 cm (H)
SHIPPING WEIGHT	639.3 lbs (290 kg)
WARRANTY	2-year engine, 1-year limited OEM (residential) 90-day limited (commercial)


1


3


5


6


7


8

FEATURES

1. Powered by a 19.5HP 500cc OHV engine
2. Dual belt drive bearing-mounted drum chipping system that builds up kinetic force for smooth, continuous material feed
3. Extra-large feed chute with integrated safety shut-off bar handles material up to 6.25" (15.9 cm) in diameter
4. Two 12" (30 cm) hardened steel reversible chipping blades
5. Tool-free swing-open chutes with safety lockout contactors for quick access to the drum chamber for easy unjamming
6. 61" (155 cm) tall expulsion chute with 180° deflector adjustability for high-volume, controlled discharge
7. 13 x 5.00-6 front flip-up wheels and 19 x 7.00-8 rear D.O.T. tires for stability on any terrain
8. Tow-behind design with 2" (5.08 cm) ball coupler
9. OSHA-compliant safety features including extended feed chute, safety stop bar, ignition lockout, and safety lockout chutes
10. Includes 2-year engine and 1-year limited OEM residential warranty, and 90-day limited commercial warranty
11. **NOT HIGHWAY TOWABLE AND MAX SPEED 25MPH (40KM/H)**

2-YEAR ENGINE WARRANTY

1-YEAR PARTS WARRANTY